GLOBAL GREEN TAG INTERNATIONAL



Tesrol Superclean

Superclean is a high pressure laminate decorative board. Superclean high pressure laminate decorative board is a high pressure laminate adhesively bound to a Moisture Resistant Medium Density Fibreboard. It is available for both horizontal and vertical applications for a variety of cabinetry products like kitchen benchtops, doors, office furniture and fitouts. It comes with a 7 year warranty for residential applications and 1 year warranty for commercial applications.

Products/Ranges:	Superclean
Product Stages Assessed:	Manufacturing + In-Use
Product Type:	High Pressure Laminate Board
CSI Masterformat:	06 40 00
Licenced Site/s:	Wetherill Park, Australia
Licence Number:	TES:TS01:2023:PH
Licence Date:	23rd October 2023
Valid To:	23rd October 2025
Standard:	GGT International v4.0
Screening Date:	17th October 2023
PHD URL:	https://www.globalgreentag.com/certificate/2386





1000/	entory Threshold: Ippm Product Level	Inventory Method: Nested Materials
-------	---	---------------------------------------

GreenTag Banned List Compliant.

SreenTag PHD recognized by WELL * & LEED * Material Transparency & Optimization credits included below:

Meets Green Star^{*} 'Buildings v1.0' as Recognized for ~ Credit 9: Responsible Finishes; as a Compliant Technical Document (Audited) for ~ Credit 13: Exposure to Toxins and 'Design & As Built v1.3' and 'Interiors v1.3' ~ Indoor Pollutants.

Meets IWBI * WELL * v1.0 as Recognized for ~ Feature 26 (Part 1); Feature 97 (Part 1); as a Compliant Technical Document (Audited) for ~ Feature 11 (Part 1); Feature 4 (Part 5); Feature 25 (Part 2, 3, 4), and, meets IWBI * WELL * v2.0 as Recognized for ~ X07 (Parts 1, 3); X08 (Part 2); as a Compliant Technical Document (Audited) for ~ X01 (Part 1); X05 (Part 1, 2); X06 (Part 2); X07 (Part 2); X08 (Part 1).

Meets USGBC LEED * v4.0 and v4.1 Rating Tool Credit as Recognized for MR Credit: Building Product Disclosure and Optimisation - Material Ingredients - Option 1: Material Ingredient Reporting, Option 2: International ACP - REACH Optimisation.

Independent third party assessment for worker, user, and environmental exposure to any Carcinogens, Mutagens, Reproductive Toxicant or Endocrine Disruptors.

INGREDIENT HAZARD DISCLOSURE, RISK ASSESSMENT: See over for explanation. INGREDIENT HAZARD DISCLOSURE 6% 18% 2% 75% · · · · · RISK ASSESSMENT IN USE HEALTH (INCL VOCS): HEALTHRATE 100%

Declared by: Global GreenTag International Pty Ltd



David Baggs CEO Verified compliant with: ISO 14024 & ISO 17065

1.0 Scope

The Global GreenTag International (GGT) Product Health Declaration (PHD) has been designed to provide an additional level of service to the green product sector in facilitating an easier understanding of both the hazard and risks associated with any certified products, and is intended to indicate:

- Chemical hazards of both finished product and unique ingredients to a minimum level of 100ppm for final product throughout the product life cycle (including any VOC or other gaseous emissions);
- An assessment of exposure or risk associated with ingredient handling, product use, and disposal in relation to established mitigation and management processes;

It is not intended to assess:

- i. substances used or created during the manufacturing process unless they remain in the final product; or
- ii. substances created after the product is delivered for end use (e.g., if the product unusually degrades, combusts or otherwise changes chemical composition).

GGT PHDs are only issued to products that have passed GGT Standards' certification requirements. The Level of Assessment (BronzeHEALTH, SilverHEALTH GoldHEALTH or PlatinumHEALTH) of a PHD rating relates ONLY to a Human Health Toxicity Assessment and is declared separately and not equivalent to the overall Bronze, Silver Gold or Platinum Green Tag Certification Mark Tier Levels of LCARate.

1.2 Preparing a PHD

GGT PHDs are prepared in the format of a transparency document which utilizes Hazard Classifications from the UN Globally Harmonised System of Classification and Labelling of Chemicals (GHS). Hazard Classifications are then risk assessed with a focus on the In Use stage for an outcome of Certification. Assessments are undertaken by GGT Qualified Exemplar Global Lead Auditors and subsequently accepted for Certification by the GGT Program Director (also a Qualified Exemplar Global Lead Auditor) under the International Standard v4.0/4.1, Personal Products Standard v1.0/1.1, and Cleaning Products Standard v1.1/1.2 and above Program Rules.

1.3 External Peer Review

Every GGT PHD is independently peer-reviewed by an external Consultant Toxicologist and Member of the Australasian College of Toxicology & Risk Assessment.

2.0 Declaration of Ingredients

Where a manufacturer wishes recognition under a rating program that requires transparency of ingredients, such as LEED * v4.0 & v4.1, WELL * v1.0 & v2.0, Green Star *, the following information is declared from the audit:

Colour	Ingredient Hazard Disclosure
Green	Level 4 The hazard level of this ingredient indicates that the ingredient has no toxic hazard statements with no identified health effects.
Yellow	Level 3 The hazard level of this ingredient indicates that the ingredient is mildly toxic and/or has short/medium term reversible health effects.
Orange	Level 2 The hazard level of this ingredient indicates that the ingredient is moderately toxic and/or with a moderate health effects.
Red	Level 1 The hazard level of this ingredient indicates that the ingredient is highly toxic with a potential for severe health effects.
Black	Level 0 The hazard level of this ingredient indicates that the ingredient is highly toxic with a potential for severe health effects and is banned from being detectable above trace amounts in the final product.
Grey	Grey Chemical Not able to be categorised due to lack of toxicity impact information.
Colour	Risk Assessment & In Use Health Assessment Outcome
Green	No Concerns The risk assessment outcomes for the hazard level and percentage of ingredient used in the product after risk assessment is considered highly unlikely and therefore without concerns.
Yellow	Human Health Comment The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered low with an unlikely potential risk.
Orange	Issue of Concern or Issue of Concern Minimised The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered Iow to high with a higher than unlikely potential for risk.
Red	Red Light Comment or Red Light Comment Minimised The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered low to extremely high with a moderate potential for risk.
Dark Red	Red Light Exclusion The risk assessment outcome for the hazard level and percentage of ingredient used in the product is after risk assessment considered medium to extremely high with a likely potential for risk.
Grey	Grey Chemical Not able to be categorised due to lack of toxicity impact information.
Black	Banned Ingredients Level 0 Hazard Level categorised chemicals such as Substances of Very High Concern in the International Standard v4.0/v4.1 and/or Petroleum, Parabens plus a wide range of additional compounds stipulated by the Personal Products Standard v1.0/1.1 and Cleaning Products Standard v1.1/1.2

Global GreenTag International Pty Ltd (Global GreenTag) is not a medical professional organisation. Global GreenTag does not purport to provide medical advice, and makes no warranty, representation, or guarantee regarding the declaration that it provides in relation to any allergies, chemical sensitivities or any other medical condition, nor does Global GreenTag assume any liability whatsoever arising out of the application or use of any product or piece of equipment that has been chemically assessed by Global GreenTag.

The chemical assessments carried out provide transparent information peer reviewed by a consultant toxicologist regarding the chemical make-up and ingredients of certain materials and products, but such assessments are not to be taken as any form of medical assessment or health advice and are not targeted towards providing specific solutions to allergenic conditions or any other type of medical concerns.

Users must carry out their own investigations if they are concerned about specific medical conditions and the impact of certain products or ingredients in relation to specific medical concerns.

Global GreenTag takes no responsibility and is not liable in any way with respect to any medical or health issues arising from a person's use of materials or products that have been chemically assessed by Global GreenTag. Global GreenTag shall not be liable for any direct, indirect, punitive, incidental, special or consequential damages to property or life whatsoever, arising out of or connected with the use or misuse of any materials or products that have been assessed by Global GreenTag.



Ingredient Name	CAS Number OR Function	Proportion in finished product	GHS, IARC & Endocrine Category	REACH	Ingredient Hazard Disclo- sure	Risk Assess- ment	In Use Health Assessment	Comment
Material: Medium Density	Fibreboard							
Softwood	Wood Fibre	50-70%	None	ОК	_	_	_	The wood is PEFC Chain of Custody Certified. When in its pressed board form there is no human health toxicity concerr Wood when it's cut can produce wood du and chronic exposure can increase the likelihood of nasal cavity cancer, however Tesrol's declared and provided supporting evidence that saw cutting of the material is not involved durin the manufacturing stage. During the In Use stage of the consumer the risk of wood dust exposure is unlikely.
								Recycled Content: None Nanomaterials: No
Water	7732-18-5	5-15%	None	ОК	_	_	_	There are no hazard statements or con- cerns for the moisture within the finished panel for human health toxicity in the In Use stage.
								Recycled Content: None Nanomaterials: No
Urea, polymer with form- aldehyde and 1,3,5-tri- azine-2,4,6-triamine	25036-13-9	5-15%	H319 (Eye Dam. 2A), H412 (Aquatic Chronic 3), H315 (Skin Irrit. 2)	ОК			_	The human health toxicity hazard state- ments H315 and H319 are considered to seldom be an issue during the In Use stag because these hazard statements apply when the adhesive is as a liquid. Once the adhesive has fully dried to a solid there ar no concerns for human health toxicity in the In Use stage.
								Recycled Content: None Nanomaterials: Unknown
Paraffin waxes and Hydrocarbon waxes	8002-74-2	1-5%	H319 (Eye Irrit. 2)	ОК	_	_	_	The human health toxicity hazard state- ments H319 are considered to seldom be an issue during the In Use stage because the wax is not expected to be at concen- trations of exposure which when touched touched on the wood could cause any eye irritation. There are no concerns for huma health toxicity in the In Use stage.
								Recycled Content: None Nanomaterials: Unknown
Material: Adhesive								
4,4'-methylenediphenyl diisocyanate; diphenyl- methane-4,4'-diisocy- anate	101-68-8	0.01-1%	H351 (Carc. 2) H332 (Acute Tox. 4) H335 (STOT SE 3) H373 (STOT RE 2) H315 (Skin Irrit. 2) H319 (Eye Irrit. 2) H334 (Resp. Sens. 1) H317 (Skin Sens. 1)	ОК	_	_	_	Exposure to this substance for consumer use has been evaluated under REACH by the Member State competent authority of Estonia for the Substance Evaluation Conclusion document which determined under 7.12.1.2 that exposure was negligib with no concerns for consumers. The highest risk for this substance is during th worker stage and from inhalation. There are no concerns for human health toxicity identified in the In Use stage.
								Recycled Content: None Nanomaterials: Unknown
Propriety	Adhesive for Wooden Boards	0.01-1%	None	ОК	_	_		The manufacturer has declared no addi- tional substances ingredients with hazard down to 0.01%. There are no concerns for human health toxicity indentified in the lu Use stage.
								Recycled Content: None Nanomaterials: No
Material: High Pressure La	minate							
Paper	Paper	5-15%	None	OK	_	_	_	The manufacturer has provided a Chain or Custody certificate for the paper. There ar no concerns for human health toxicity in the In Use stage for this material.
								Recycled Content: None Nanomaterials: Unknown



Formaldehyde, oligomer- ic reaction products with phenol	9003-35-4	5-15%	H319 (Eye Dam. 2A) H317 (Skin Sens. 1)	ОК	 	_	The hazard statements are most applicable when the adhesive is a liquid. Within the finished product the resin is cured and presents negligible probability of contact- ing the consumer as a liquid within the In Use stage. There are no concerns for human health toxicity in the In Use stage. Recycled Content: None Nanomaterials: Unknown
Paper-Pigmented	Paper	1-5%	None	ОК			The manufacturer provided a Chain of Cus- tody certificate for the paper. The manufac- turer has declared no additional substances ingredients with hazards down to 0.01%. There are no concerns for human health toxicity indentified in the In Use stage. Recycled Content: None Nanomaterials: Unknown
1,3,5-Triazine-2,4,6-tri- amine, polymer with formaldehyde	9003-08-1	5-15%	H410 (Aquatic Chronic 1) H412 (Aquatic Chronic 3) H317 (Skin Sens. 1) H315 (Skin Irrit. 2) H319 (Eye Dam. 2A) H334 (Resp. Sens. 1)	ОК			This chemical is currently largely unclas- sified with sizable proportions of aquatic toxicity hazard statements, however no identifiable consensus for human health toxicity risk according to ECHA's summary of classification and labelling. The minority of hazard statements which could apply have been listed as a precautionary ap- proach however they are expected to apply when the substance is either in contact as a powder or a liquid. Once cured there is negligible probability of contacting the consumer as a liquid or a powder in the In Use stage. There are no concerns for human health toxicity in the In Use stage. Recycled Content: None Nanomaterials: Unknown

* No GHS H-Statement classification

Comments:

The Superclean product has been tested to ASTM D7706-11, which follows the same analytical technique as the small chamber method ASTM D5116, for both formaldehyde emissions and Total VOC as Toluene. The test reports a formaldehyde emissions factor of 0.06 mg/m2/hr which is below the reference standard for ASTM D5116 in the Global GreenTag International Standard v4.0 of ≤ 0.1 mg/m2/hr for E1 (see Table 7.4.1). It is not below 50% of the E1 standard which is ≤ 0.05 mg/m2/hr. The test reports a TVOC as Toluene of 0.19 mg/m2/hr which is below the Global GreenTag International Standard v4.0 of ≤ 0.5 mg/m2/hr. The test reports a TVOC as Toluene of 0.19 mg/m2/hr which is below the Global GreenTag International Standard v4.0 of ≤ 0.5 mg/m2/hr for a fitout item (see Table 7.10.1).

